

THESE INSTRUMENTS MEET OR EXCEED THE REQUIREMENTS OF UNITED INSTRUMENTS, INC. SPECIFICATIONS, UI5934, UI5934D, OR UI5950, SUBJECT TO THE FOLLOWING AMENDMENTS:


1. INSTRUMENTS SHALL BE EQUIPPED WITH LIGHTING BEZEL AND LIGHT TRAY ASSEMBLIES, BOTH MANUFACTURED BY BISHOP AVIATION, HOT SPRINGS, ARKANSAS.

LEAD WIRE: PER SAE AS22759/16-24, BLACK AND WHITE.
 WHITE - RATED LIGHTING VOLTAGE
 BLACK - GROUND

2. EXTERNAL DIMENSIONS OF THE BEZEL LIGHTED INDICATOR SHALL BE AS SHOWN ABOVE.
3. PART AND CODE NUMBERS OF THE BEZEL LIGHTED INDICATORS ARE AS LISTED ON PAGE 2.
4. RATED LIGHTING VOLTAGE SHALL BE MARKED ON TOP OF THE LIGHT TRAY ASSEMBLY.

ADDENDUM SHEETS TO: UI5934
 UI5934D
 UI5950

| | | | | | | | | | |
|------|---------|--|----------------------|--------|-------------------------|--------------------|----------|--------------------|--------|
| E | 3/27/06 | CHNGD LEAD WIRE & P/N | <i>[Signature]</i> | | | | PREP. BY | <i>S. Barakchi</i> | 2/6/86 |
| C | 9-10-93 | CANCEL REV. B AND CHNGD UI P/N (WAS: -1) | <i>[Signature]</i> D | 623-97 | ADDED NOTE 2 & 3 (P. 2) | <i>[Signature]</i> | APPR. BY | <i>T. Sawawa</i> | 2-7-86 |
| B | 8-20-93 | ADDED DAMPENED UNITS | <i>[Signature]</i> A | 2-7-86 | SPEC RE-ISSUED | <i>[Signature]</i> | CHECKER | | |
| REV. | DATE | | CHK. | REV. | DATE | CHK. | | NAME | DATE |

| | | | |
|---|---|--|-----------------------------|
|  <p>UNITED INSTRUMENTS, INC. 3625 Comotara Avenue Wichita, Kansas 67226</p> | <p>TITLE: INDICATOR - ALTIMETER, BEZEL LIGHTED / DAMPENED</p> | <p>SPEC. NO: UI5934BL (REF. UI5934, UI5934D, AND UI5950)</p> | <p>ISSUE E</p> |
| | | <p>PAGE 1 OF 2 PAGES</p> | |

| BEZEL LIGHTING INDICATOR | | | | | | NON-LIGHTING INDICATOR CODE NO. |
|--------------------------|-------------|-------|--------|--------|--------|---------------------------------------|
| PART NUMBER | CODE NUMBER | | | | | |
| | LESS L/TRAY | 5 VDC | 12 VDC | 14 VDC | 28 VDC | |
| 5934A-3 | A.150 | A.151 | A.114 | A.152 | A.153 | A.61 |
| 5934-3 | A.154 | A.155 | A.112 | A.156 | A.157 | A.68 |
| 5934M-3 | A.189 | A.190 | A.119 | A.192 | A.193 | A.73 |
| 5934P-3 | A.194 | A.195 | A.196 | A.197 | A.198 | A.83 |
| 5934PM-3 | A.199 | A.200 | A.201 | A.202 | A.203 | A.84 |
| 5934AM-3 | A.204 | A.205 | A.117 | A.206 | A.207 | A.85 |
| 5934PA-3 | A.122 | A.209 | A.210 | A.211 | A.184 | A.86 |
| 5934PAM-3 | A.124 | A.213 | A.214 | A.215 | A.185 | A.87 |
| 5934PA-3D | A.217 | A.218 | A.219 | A.220 | A.221 | A.127 |
| 5934PAM-3D | A.222 | A.223 | A.224 | A.225 | A.226 | A.128 |
| 5934-3D | A.227 | A.228 | A.145 | A.229 | A.230 | A.137 |
| 5934A-3D | A.231 | A.232 | A.233 | A.234 | A.235 | A.138 |
| 5934M-3D | A.236 | A.237 | A.238 | A.239 | A.240 | A.139 |
| 5934AM-3D | A.241 | A.242 | A.243 | A.244 | A.245 | A.140 |
| 5934D-3 | A.246 | A.247 | A.136 | A.248 | A.249 | A.129 |
| 5934PD-3 | A.250 | A.251 | A.252 | A.187 | A.253 | A.130 |
| 5934AD-3 | A.254 | A.255 | A.256 | A.257 | A.258 | A.131 |
| 5934PAD-3 | A.259 | A.260 | A.261 | A.188 | A.186 | A.132 |
| 5934D-3D | A.262 | A.263 | A.264 | A.265 | A.266 | A.141 |
| 5934PD-3D | A.267 | A.268 | A.269 | A.270 | A.271 | A.142 |
| 5934AD-3D | A.272 | A.273 | A.274 | A.275 | A.276 | A.143 |
| 5934PAD-3D | A.277 | A.278 | A.279 | A.280 | A.281 | A.144 |
| 5950 | A.282 | A.283 | A.284 | A.285 | A.286 | A.178 |
| 5950M | A.287 | A.288 | A.289 | A.290 | A.291 | A.179 |
| 5950D | A.292 | A.293 | A.294 | A.295 | A.296 | A.180 |
| 5950P | A.297 | A.298 | A.299 | A.300 | A.301 | A.181 |
| 5950PM | A.302 | A.303 | A.304 | A.305 | A.306 | A.182 |
| 5950PD | A.307 | A.308 | A.309 | A.310 | A.311 | A.183 |

NOTES:

1. The lighted indicators are the same as unlighted indicators specified by United Instruments' specifications; UI5934, UI5934D, and UI5950, except the lighting bezel and applicable light tray are installed instead of the non-lighting bezel.
2. The basic bezel lighted indicator is equipped with a plastic wedge with uncoated cover glass. The lighting bezel and light tray part numbers are BA3-001-003A and BA(VOLTAGE)-24T-BW3 of Bishop Aviation, respectively. E
3. The lighted indicator with an HEA glass wedge is identified with a Letter 'H' suffixed to the code number of the basic lighted indicators listed in the above table. The lighting bezel and light tray part numbers are BA3-001-003G-901 and BA(VOLTAGE)-24T-BW3G of Bishop Aviation, respectively. E

| | | | |
|---|---|--|------------|
| CUSTOMER ACCEPTANCE SPECIFICATION UNITED INSTRUMENTS, INC. | TITLE: INDICATOR-ALTIMETER, BEZEL LIGHTED | SPEC. NO: UI5934BL (REF UI5934, UI5934D, AND UI5950) | ISSUE E |
| | | PAGE 2 OF 2 | PAGES |